



表示方式：
 MI - B - M3 - 6
 ↓ ↓ ↓ ↓
 型号 材质 螺纹 长度
 代号

公制规格表：

螺纹*牙距	型号			螺纹代号	长度 L ± 0.1	E -0.13	螺纹孔径
	黄铜	不锈钢	碳钢				
M2*0.4	MI-B	MI-S	MI-C	M2	2 3 4 5 6 7 8 9 10 11 12	4.00	1.6/1.67
M2.5*0.45	MI-B	MI-S	MI-C	M2.5	2.5 3 4 5 6 7 8 9 10 11 12 12.7	4.50	2.05/2.13
M3*0.5	MI-B	MI-S	MI-C	M3	3 4 5 6 7 8 9 10 11 12 12.7 15 18	4.75	2.5/2.59
M4*0.7	MI-B	MI-S	MI-C	M4	3 4 5 6 7 8 9 10 11 12 12.7 15 18 20	6.35	3.3/3.4
M5*0.8	MI-B	MI-S	MI-C	M5	3 4 5 6 7 8 9 10 11 12 12.7 15 18 20 25	7.05	4.2/4.3
M6*1.0	MI-B	MI-S	MI-C	M6	4 5 6 7 8 9 10 11 12 12.7 15 18 20 25 30	9.05	5.0/5.1
M8*1.25	MI-B	MI-S	MI-C	M8	5 6 7 8 9 10 11 12 12.7 15 18 20 25 30 32	11.05	6.8/6.9

美制规格表

螺纹-牙数	型号			螺纹代号	长度编码 (编码/32为实际长度) L ± .004								E -.005	螺纹孔径
	黄铜	不锈钢	碳钢		.125	.187	.250	0.3	.375	.500	.625	.750		
#2-56	MI-B	MI-S	MI-C	256	4	6	8	10	12	16	20	24	.157	.067/.0737
#4-40	MI-B	MI-S	MI-C	440	4	6	8	10	12	16	20	24	.188	.086/.0939
#6-32	MI-B	MI-S	MI-C	632	4	6	8	10	12	16	20	24	.217	.105/.114
#8-32	MI-B	MI-S	MI-C	832	4	6	8	10	12	16	20	24	.250	.131/.139
#10-32	MI-B	MI-S	MI-C	032	4	6	8	10	12	16	20	24	.278	.157/.164
1/4-20	MI-B	MI-S	MI-C	0420	4	6	8	10	12	16	20	24	.375	.197/.207
5/16-18	MI-B	MI-S	MI-C	0518	4	6	8	10	12	16	20	24	.437	.260/.265
3/8-16	MI-B	MI-S	MI-C	0616	4	6	8	10	12	16	20	24	.500	.309/.321

安装方式：

