



Part Number Designation : SHK - B - M4 - 8.1

↓                      ↓                      ↓                      ↓  
 型号                  材质                  螺纹                  长度

公制规格表 (单位mm):

类型	螺纹	长度 L ±0.1	外径 ΦE ±0.1	导向柱 ΦC ±	头径 ΦA ±	头厚 B ±0.05	塑胶预留孔			
							F +0.1	D (Min)	T ±0.05	最少肉厚
SHK:	M1.6	2.0 2.2 2.5 3.0	2.50	2.10	3.0	0.40	2.15	3.2	0.40	0.80
	M2	2.0 3.0 4.0 5.0	3.6	3.1	4.8	0.53	3.2	5.0	0.53	1.3
	M2.5	2.0 3.0 5.0 5.7	4.6	3.9	5.5	0.61	4.0	5.7	0.61	1.6
SHK-B	M3	4.0 4.8 5.7 6.0	4.6	3.9	5.5	0.61	4.0	5.7	0.61	1.6
SHK-S	M4	4.0 4.8 5.8 8.1	6.3	5.5	7.1	0.91	5.6	7.3	0.91	2.1
SHK-A	M5	5.8 6.8 9.5	7.1	6.3	7.9	1.09	6.4	8.1	1.09	2.6
	M6	6.8 9.5 12.7	8.7	7.9	9.5	1.35	8.0	9.7	1.35	3.3
	M8	12.7	10.2	9.5	11.1	1.35	9.6	11.3	1.35	4.5
	M10	12.7	12.6	11.8	14.0	1.60	11.9	14.3	1.60	6.0
	M12	15.9	16.7	15.8	19.0	2.00	16.0	19.3	2.00	8.0

美制规格表 (单位 英寸) :

类型	螺纹	螺纹 代号	长度 L ±.004	外径 ΦE ±.004	导向柱 ΦC ±.002	头径 ΦA ±.004	头厚 B ±.002	塑胶预留孔			
								F +.004	D (Min)	T ±.002	最少 肉厚
SHK:	2-56	256	.100 .125 .157	.141	.123	.187	.021	.126	.195	.021	.051
	4-40	440	.096 .140 .170 .226 .250	.181	.154	.218	.024	.157	.226	.024	.163
	6-32	632	.150 .226 .250 .281	.214	.185	.250	.030	.189	.258	.030	.071
SHK-B	8-32	832	.185 .250 .321	.248	.218	.281	.036	.220	.289	.036	.083
SHK-S	10-24	024	.250 .375	.278	.249	.312	.043	.252	.320	.043	.102
SHK-A	10-32	032	.226 .250 .375	.278	.249	.312	.043	.252	.320	.043	.102
	1/4-20	0420	.250 .500	.341	.312	.375	.053	.315	.383	.053	.130
	5/16-	0518	.500	.403	.374	.437	.053	.378	.445	.053	.177
	3/8-16	0616	.500	.494	.465	.551	.063	.469	.559	.063	.236
	1/2-13	0813	.625	.657	.622	.748	.079	.630	.754	.079	.315

塑胶预留孔的样式:

